GUCBIR GENERATOR

GJP50-LS

INDUSTRIAL RANGE

Perkins

GENERATING SETS

WATER COOLED | THREE PHASES | 50 HZ | DIESEL

Service		Standby	Prime
Power	*kVA*	49,6	45
Power	*kW*	39,7	36
Rated Speed	*r.p.m*	1500	
Standart Voltage	*V*	400/230	
Rated At Power Factor	*Cos Phi*	0,8	

GUCBIR Company with quality certification ISO 9001
GUCBIR gensets are compliant with EC mark which includes the following directives:

- 2006/42/EC Machinery safety.
- 2014/30/EU Electromagnetic compatibility.
- 2014/35/EU electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2005 normative: 1000 mbar, 25°C, 30% relative humidity.
G2 class load acceptance in accordance with ISO 8528-5:2013

+90 216 312 7979
info@gucbirjenerator.com

GUCBIR JENERATOR SAN. TIC. LTD. ŞTİ.
Serifali Mahallesi, TavukCuyolu Cad. No:200 - Umraniye / ISTANBUL / TURKIYE
T: +90 216 312 79 79 | F: +90 216 312 79 77
info@gucbirjenerator.com | www.gucbirjenerator.com

GUCBIR GENERATOR

GJP50-LS

INDUSTRIAL RANGE

Perkins

SPECIFICATIONS

Perkins **Engine**

LEROY SOMER **Alternator**

Engine		Specifications
Standby Power/Prime Power	*kWm*	46,5 / 42,2
Manufacturer		Perkins
Model		1103A-33TG1
Engine Type		4 Stroke - Diesel
Injection Type		Direct Injection
Aspiration Type		Turbo Charged
Number of cylinder		3
Bore and Stroke	*mm*	105X127
Displacement	*L*	3,3
Cooling System		Water Cooling
Hecting Power	*Watt*	1000W
Fuel Consumption 50% PRP	*l/h*	4,06
Fuel Consumption 75% PRP	*l/h*	5,61
Fuel Consumption 100 % PRP	*l/h*	7,2
Fuel Consumption Standby	*l/h*	8,1
Oil fuel consumption ratio	*%fuel*	≤0.15%
Total oil capacity including tubes, filters	*L*	8,3
Total coolant capacity	*L*	10,2
Governor	*Type*	Mechanical and Electronic
Electric system voltage(V)	*V*	12

Alternator		Specifications
Manufacturer		Leroy Somer
Model		TAL-A42-F
Output Voltage	*V*	230/400
Frequency	*HZ*	50
Automatic Voltage Regulation	*±%*	1
Alternator Standby Power	*kVA*	50
Alternator Continuous Power	*kVA*	45
Power Factor	*Cosq*	0,8
Number of Wires		12
Winding		2/3
Protection Class		IP23 / H
Excition System		Self Excited
AVR Model		R120
Performance - PF 0,8 / %75 Load	*%*	89,3

Prime Power (PRP):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2005, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.

Note: All data based on operation to ISO 3046/1, BS 5514 and DIN 6271 standard reference conditions

+90 216 312 7979
info@gucbirjenerator.com

GUCBIR JENERATOR SAN. TIC. LTD. ŞTİ.
Serifali Mahallesi, TavukCuyolu Cad. No:200 - Umraniye / ISTANBUL / TURKIYE
T: +90 216 312 79 79 | F: +90 216 312 79 77
info@gucbirjenerator.com | www.gucbirjenerator.com

GUCBIR GENERATOR

GJP50-LS

INDUSTRIAL RANGE

Perkins

DIMENSIONS







OPEN SET

LxWxH	*mm*	1800x900x1500
Weight	*kg*	850
Fuel Tank	*lt*	200





CANOPIED

LxWxH	*mm*	2225x950x1640
Weight	*kg*	1160
Fuel Tank	*lt*	140

Sound Proof Canopy

- Special design for minimizing acoustic level.
- Galvanized steel construction further protected by polyester powder coat paint.
- Black finish stainless steel locks and hinges.
- Control panel viewing window in a lockable access door.
- Emergency stop push button (red) mounted on enclosure exterior.
- Lifting, drag and jacking points on base frame.
- Radiator fill via removable, flush mounted rain cap fitted with compression seal.
- Acoustic insulation with moisture-repellent and non-flammable material

+90 216 312 7979
info@gucbirjenerator.com

GUCBIR JENERATOR SAN. TIC. LTD. ŞTİ.
Serifali Mahallesi, TavukCuyolu Cad. No:200 - Umraniye / ISTANBUL / TURKIYE
T: +90 216 312 79 79 | F: +90 216 312 79 77
info@gucbirjenerator.com | www.gucbirjenerator.com

GUCBIR GENERATOR

GJP50-LS

INDUSTRIAL RANGE

Perkins

CONTROL UNIT

DATAKOM — Control Unit

GB500 - DATAKOM

ATS unit with uninterrupted transfer	Internet Central Monitoring
AMF unit with uninterrupted transfer	SMS / E-mail message sending
Remote / Manuel start controller	Flexible with plug-in modules
Engine controller	Free PC software: Rainbow Plus
GSM-GPRS-GPS-Ethernet Port	Modbus RTU
8 configurable digital inputs	

ATS PANEL

GUCBIR automatic transfer switches are reliable, rugged, versatile, and compact assemblies for transferring essential loads and electrical distribution systems from one power source to another. GUCBIR 's contac - tor-based transfer switch is rated 40–3600A and can be supplied in separate enclosures for standalone applica - tions or can be supplied as an integral component Contactors inside the ATS panels are well known and internationally recognized brands such as ABB, SIEMENS, SCHNEIDER, GE, LS, HYUNDAI and ANDELI.

ABB telergon ANDELI HYUNDAI socomec SIEMENS LS Industrial Systems

OPTIONAL EQUIPMENTS

Some Optional Equipments that GUCBIR prov ides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Trailer,
- Remote monitoring.
- SMPS 12/24V 10A

Control Panel

- DeepSea 7320
- Datakom D700/D300/D309/D200
- ComAp AMF9
- ComAp AMF25

+90 216 312 7979
info@gucbirjenerator.com

GUCBIR JENERATOR SAN. TIC. LTD. ŞTİ.
Serifali Mahallesi, TavukCuyolu Cad. No:200 - Umraniye / ISTANBUL / TURKIYE
T: +90 216 312 79 79 | F: +90 216 312 79 77
info@gucbirjenerator.com | www.gucbirjenerator.com